



## ASTR Packaged Condensing Units

### R404a Medium Temperature (Compact Range)

Model	Displ. (cc)	HP	Capacity @-5°C (Watts)
AU100TM	25.90	1 1/4	2716
AU150TM	34.40	1 1/2	3529
AU200TM	43.50	2	3870

32°C ambient

### R404a Low Temperature (Compact Range)

Model	Displ. (cc)	HP	Capacity @-23.3°C (Watts)
AU100TL	34.40	1 1/2	1600
AU200TL	53.20	2	2395


32°C ambient

#### Compact Range packaged condensing units include:

Hermetique compressor, drier, sight glass, fan speed control, passivated fins & dual pressure control

Suits standard A/C bracket

For further specifications, see the [Compact Range Catalogue](#)



Wholesale-Consulting-Engineering

For more information, please call:  
Refrigeration Distributors P/L (02) 97437911  
1/10 Ferngrove Place, Chester Hill NSW 2162  
<http://www.rdl.com.au>





## R404a Scroll Condensing Unit (Commercial Range)

Model	HP	Capacity @-5°C (Watts)
NF200D NF200S	2.0	4270
NF250D NF250S	2.5	5525
NF300D NF300S	3.0	6400
NF350S	3.5	7265
NF400S	4.0	8755
NF500S	5.0	10870
NF600S	6.0	12770
NF700DC	7.0	15800
NF800DC	8.0	19200
ND900DC	9.0	21600
NF1000DC	10.0	25300


32°C ambient

- D: Single Phase
- S: Three Phase

### Commercial Range packaged condensing units include:

Danfoss scroll compressor, accumulator, oil separator, dual pressure control, fan speed control, drier, sight glass, oil filled gauges, nitrogen holding charge, gomax flexible hoses, passivated fins, Panasonic DC Fans, Fan Speed Controller

For further specifications, see the [Commercial Range Catalogue](#)



For more information, please call:  
Refrigeration Distributors P/L (02) 97437911  
1/10 Ferngrove Place, Chester Hill NSW 2162  
<http://www.rdl.com.au>





## R404a Dorin Packaged Unit (Industrial Hybrid Range)

Model	HP	Capacity @-5°C (Watts)	Capacity @-25°C (Watts)
NFB500SGMH	5	13660	5490
NFB750SGMH	7.5	18520	7250
NFB1000SGMH	10	26270	10730
NFB1500SGMH	15	29810	12340
NFB2000SGMH	20	35350	14670
NFB2500SGMH	25	44850	17780
NFB3000SGMH	30	50300	19700
NFB3500SGMH	35	65220	26590


38°C ambient temperature, ratings based at 10KTD condensing temp.

### Industrial Range packaged condensing units include:

Dorin semi hermetic compressor, condenser designed with liquid subcooling, soft starter fitted to 15hp onwards, accumulator, liquid receiver, oil separator, Danfoss dual pressure control, Saginomiya fan speed control, demountable suction line drier, liquid line drier and sight glass, ABB contactors and gauges

For further specifications, see the [Industrial Range Catalogue](#)

For more information, please call:  
Refrigeration Distributors P/L (02) 97437911  
1/10 Ferngrove Place, Chester Hill NSW 2162  
<http://www.rdl.com.au>



Wholesale-Consulting-Engineering

